

(12) United States Patent Ogawa et al.

(54) POWER SUPPLY STRUCTURE FOR SLIDING DOOR

(71) Applicants: YAZAKI CORPORATION,

Minato-ku, Tokyo (JP); AISIN SEIKI KABUSHIKI KAISHA, Kariya-shi,

Aichi (JP)

(72) Inventors: Tatsuo Ogawa, Kosai (JP); Akitomo

Iijima, Kosai (JP); Yushi Tanamura,

Kariya (JP)

Assignees: Yazaki Corporation, Minato-ku, Tokyo

(JP); AISIN SEIKI KABUSHIKI KAISHA, Kariya-shi, Aichi-ken (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/027,054

(22) PCT Filed: Oct. 3, 2014

(86) PCT No.: PCT/JP2014/076565

§ 371 (c)(1),

(2) Date: Apr. 4, 2016

(87) PCT Pub. No.: WO2015/053191

PCT Pub. Date: Apr. 16, 2015

Prior Publication Data (65)

> US 2016/0236630 A1 Aug. 18, 2016

(30)Foreign Application Priority Data

Oct. 11, 2013 (JP) 2013-214056

(51) Int. Cl.

B60J 5/00 (2006.01)B60R 16/02

(2006.01)

(Continued)

(10) Patent No.:

US 9,637,070 B2

(45) Date of Patent:

May 2, 2017

(52) U.S. Cl.

CPC B60R 16/02 (2013.01); B60R 16/027

(2013.01); H02G 11/00 (2013.01)

Field of Classification Search

CPC B60R 16/02; B60R 16/027; H02G 11/00 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

2009/0194327 A1* 8/2009 Tsubaki H02G 11/00

2009/0223132 A1 9/2009 Aoki et al.

FOREIGN PATENT DOCUMENTS

JP 2008-148539 A 6/2008 JP 2009-65814 A 3/2009

(Continued)

OTHER PUBLICATIONS

International Search Report of PCT/JP2014/076565, dated Dec. 22,

2014. [PCT/ISA/210].

(Continued)

Primary Examiner — Lori L Lyjak

(74) Attorney, Agent, or Firm — Sughrue Mion, PLLC

(57)ABSTRACT

A power supply structure for a sliding door includes other end-side holding portion which holds the other end of the electric wire. The other end-side holding portion includes first and second turning arms which are rotatably supported directly or indirectly by the sliding door and hold the electric wire at a tip end thereof, and biasing unit which biases the first turning arm in a direction to absorb an extra length of the electric wire. The tip end of the second turning arm inclines with respect to a longitudinal direction of a vehicle at climbing-over timing at which the electric wire climbs over a predetermined climbing-over position of a lower end (Continued)

